

POLLOCK DEMO/REFURBISHED EQUIPMENT INVENTORY

	<p>WELD-O-TRON 6020 L-BAR SEALER \$1,800</p> <p>The 6020 sealer is designed for ease of operation and dependable long term service with little or no maintenance.</p> <p>FEATURES:</p> <ul style="list-style-type: none"> • Solid state, central control module • Self-compensating seal temperature and control • Heavy duty seal head design • Structural steel base with casters • Surface film unwind • Seal bar film clamps • Easy to operate • Quick-adjust sealing platform
	<p>LANTECH ST-700 AUTOMATIC SHRINK TUNNEL \$9,200</p> <p>The Lantech ST-700 is the first shrink tunnel with all the key elements at one station – ViewWindow™, air circulation, temperature and conveyor speed control.</p> <p>FEATURES:</p> <ul style="list-style-type: none"> • Increases productivity, faster set up • Consistent heat and air temperature reduces rework and waste • Accommodates a wide range of product sizes and shapes, films and production speeds with little or no adjustments required • Uniform air flow around product • Predictable shrink process results • ViewWindow™ provides clear view of shrink process and allows real-time control of packaging results
	<p>3M-MATIC 77A ADJUSTABLE CASE SEALER \$1,975</p> <p>The 3M-Matic 77a Adjustable Case Sealer is designed to apply a “c” clip of sealing tape to the top and bottom center seam of regular slotted containers. The 77A is manually adjustable to a wide range of box sizes.</p> <p>FEATURES:</p> <ul style="list-style-type: none"> • Top and bottom case taper • Case size range: Min – 6” x 6” x 4.75” Max – Unlimited x 20” x 20” • Tape width: Min – 1.5 in Max – 2 in • Tape roll maximum diameter: 15.5 inches on 3 inch core • Adjustable conveyor bed height: 20.5 - 31.5 inches • Overall dimensions: 42.5 inches long x 27.5 inches wide x 56.75 inches high
	<p>LOVESHAW LITTLE DAVID 3SB UNIFORM CASE SEALER \$2,800</p> <p>This side-belt driven tape sealer is recommended for dimensionally unstable boxes, lightweight boxes and boxes as narrow as 3-1/4". Can be used for setting up empty boxes with bottom tape only.</p> <p>FEATURES:</p> <ul style="list-style-type: none"> • Tapes boxes from 4-1/2" (114mm) to 24" (610mm) in height • Uses 2" pressure sensitive tape • Minimal operator training required • Self-centering belts and sealed drive system • CaseLocker ST® tape cartridge requires no lubrication • Single mast design allows clear access • Knife guard system of the CaseLocker ST® tape cartridge only allows the blade to be exposed only when the rollers have been depressed

PACKAGING

